TECHNICAL DATA SHEET

Infinity SPRAY PLASTER

Sprayable Plaster Designed By Infinity The Next Gen In Plastering

Infinity Spray Plaster is a ready-to-use, airless spray-applied plaster designed for interior levelling and fine finishing of walls and ceilings.



SUITABLE SUBSTRATES

Infinity Spray Plaster can be applied to both new and renovated substrates, whether painted or unpainted, including:

- Gypsum
- Plasterboard / drywall
- Old painted surfaces
- Cement
- Concrete
- Cellular concrete

No primer or sealer is required before application.

OVERCOATING

Once dry, Infinity Spray Plaster can be overcoated with all types of fillers, paints, or wall coverings.

PHYSICAL & TECHNICAL CHARACTERISTICS

- **Ready-to-use** airless spray plaster formulated with mineral components and synthetic resin
- **Characterisation** (NFT 36-005): Family III – Class 2
- **Codification** (EN 16566): G3S1V0W0A0C0R0
- **Mixing:** Ready to use, no dilution required
- **Recommended application thickness:** Up to 5 mm
- **Coverage:** Approx. 1.7 kg/m²/mm
- **Setting time:** Second coat may be applied once the first coat is hard and dry to the touch
- **Overcoating:** Paintable after 24–48 hours (once completely dry)
- **Colour:** White

USE & STORAGE CONDITIONS

- **Application tools:** Any airless spray machine with a minimum flow rate of 5 L/min. Recommended nozzles: 5.31, 5.35, 6.31, 6.35
- **Cleaning:** Clean tools immediately with water
- **Storage:** Store in original sealed packaging — Keep away from frost and direct sunlight

PACKAGING

- 20 kg buckets

RECOMMENDATIONS & APPLICATION GUIDANCE

- All times provided are indicative and depend on substrate type, coat thickness, temperature, and humidity
- Do not apply when: Temperature is below 8°C or above 35°C; Relative humidity exceeds 70%; Substrates are damp or overheated
- Not suitable for application on polystyrene, wallpaper, or exterior surfaces

SUBSTRATE PREPARATION

Prepare substrates according to standard trade practices. Surfaces must be hard, cohesive, clean, sound, and dry.

KEY BENEFITS

Ready to Use
No mixing or dilution required. Open, spray, and apply.

Fast & Efficient
Airless spray application for quick, even coverage.

Smooth Finish
Provides a fine, uniform surface ready for overcoating.

Versatile
Suitable for a wide range of interior substrates.

High Performance
Strong adhesion, minimal shrinkage, and excellent workability.

No Primer Required
Can be applied directly to most common interior substrates.

Introducing Infinity Spray Plaster:
Infinity Spray Plaster is a ready-to-use, airless spray-applied plaster designed for interior levelling and fine finishing of walls and ceilings.

INFINITY SPRAY PLASTER – SPECIFICATION

Type	All In One Spray Plaster (No-VOC)
Mix Ratio	Pre-Mixed – add DI water if necessary
Pack Sizes	20KG Buckets
Colour	White
Shelf Life & Storage	8 months in original, unopened container. Store in cool, dry conditions